

Online UPS, 6000 VA, USB + SNMP slot, terminals without cables

EG-UPS0-6000

ULTIMATE DEFENCE

- Pure sine wave output
- Provide backup power Prevents data loss
- Protects your sensitive and valuable equipment
- Perfect support for solar panel installations and other sensitive equipment that requires pure sinewave input
- Compact and reliable ideal for home and small office use



Características

- Online type UPS: double voltage conversion with pure sine wave output without switching the power
- USB interface
- Automatic AC voltage regulation (AVR)
- Intelligent overload and short-circuit protection
- Audible and visual alarms
- LCD display and LED status indication
- Internal battery with overcharge and over-discharge protection

Embalaje

Cantidad por caja, pcs	1
Volumen caja, M3	0.19982
Peso caja, kgs	61
Medidas cajas individuales LxWxH:	310x685x941 mm
Medidas caja LxWxH	310x685x941 mm
País de origen	CN
Código de barras	8716309124843
Código de aduanas	8504408590

Contenido de la caja

UPS without cords

Especificaciones

Type: online

Waveform: sine, <2% distortion at linear load (<5% non-linear), PF > 0.99

Input: AC 176 ~ 288 V, 40 70 Hz autotdetect

Output: AC 208 V / 220 V / 230 V / 240 V (settable) $\pm 1\%$, 45Hz/65Hz autosense

Switching time: near 0 ms

Backup time: 30 mins (depends on the load)

Battery: UPS with sealed lead-acid 12V/7Ah 16 pcs; 192 V DC

Charge time: 90% capacity restored in 8 hours

Input Sockets: Terminal block input Single-phase three-wire (1F + N + PE);

Output Sockets: Terminal block input; 6x C13 socket outputs

Interface communication: USB; optional slots: RS485 / dry contacts / SNMP / battery temperature compensation

Operating conditions: 0°C~40°C, at humidity 20~90%RH non condensing

Power: 6000 VA (~6000 W)

Noise: < 55 dB at 1 m distance

Dimensions: 310 x 685 x 941 mm

Product weight: 53 kg

"Cold-start" function

Certificados



Requisitos del sistema

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.